

TurretCam HL

Wired AI-powered security IP camera with hybrid illumination, True WDR, microphone, and PoE/12 V. For outdoor and indoor use.

Onvif®

GS

IR

WL

IK08

IP66

True WDR

PoE

micro SD

NDA Compliant



Product versions

TurretCam HL (5 Mp/2.8 mm) 5 MP f/2.8 mm (fixed) up to 2880 × 1620 px 25 fps (3K UHD) 100°–110°	TurretCam HL (8 Mp/2.8 mm) 8 MP f/2.8 mm (fixed) up to 3840 × 2160 px 20 fps (4K UHD) 100°–110°	TurretCam HL (5 Mp/4 mm) 5 MP f/4 mm (fixed) up to 2880 × 1620 px 25 fps (3K UHD) 75°–85°	TurretCam HL (8 Mp/4 mm) 8 MP f/4 mm (fixed) up to 3840 × 2160 px 20 fps (4K UHD) 75°–85°
--	--	--	--

Clear image with full-color details, day and night

Hybrid illumination in TurretCam HL cameras automatically switches between infrared and white light based on object recognition or motion detection. This ensures high image quality in low-light conditions and at night. The feature provides full-color footage for better object recognition and helps deter intruders when white light is activated.

IR

IR illumination range

up to 50 m (164 ft)

WL

White light illumination range

up to 50 m (164 ft)

Uncompromising security and privacy


- Passwordless camera authentication via mutual TLS (mTLS) handshake
 - TLS-encrypted video streams
 - User-controlled access to video content
 - Secure video export with digital signature verification
- Multi-tiered account protection: passcodes, biometrics, and two-factor authentication
 - Session control for additional account security
 - NDAA-compliant components and protocols

Seamless user experience

- AI-powered object recognition: humans, vehicles, and pets
 - High-resolution visual verification of alarms via video scenarios
 - Instant transition from notifications to on-site video recordings
- Camera synchronization with security system modes
 - Real-time monitoring with a customizable video wall
 - True WDR (Wide Dynamic Range) for superior image quality


Smooth archive navigation

- Proprietary JetSparrow technology for instant, secure video streaming and smooth archive navigation
- Instant access to live view
- Fast archive navigation using event timeline, calendar view, and search filters
- Dual streams for instant preview and optimized bandwidth usage
- Quick video clip export in just a few clicks



Easy installation and maintenance


- Adding to an Ajax system via QR code
- Remote control and configuration via Ajax apps
- Conformance with ONVIF® Profile G and S
- RTSP support
- Motion detection zone configuration via Ajax mobile and desktop apps
- Real-time system health monitoring with automatic state checks



Flexible video surveillance for any scale and scenario

TurretCam HL cameras use Ajax Cloud to transmit system events and JetSparrow technology for fast, secure peer-to-peer video data transmission. With AI-powered object recognition, the camera can identify humans, vehicles, and pets, ensuring only relevant activity is recorded. Strict event filtering helps save storage space and streamlines archive navigation.

Hybrid illumination provides full-color image quality day and night. The camera can be activated depending on the security mode, making video surveillance precisely selective and effective.



TurretCam HL cameras can operate without the Ajax NVR – the video archive is stored locally on a microSD card if installed.

DORI distance

Version	Detection	Observation	Recognition	Identification
TurretCam HL (5 Mp/2.8 mm)	65 m (213 ft)	26 m (85 ft)	13 m (42 ft)	6.5 m (21 ft)
TurretCam HL (5 Mp/4 mm)	86 m (282 ft)	34.4 m (112 ft)	17.2 m (56 ft)	8.6 m (28 ft)
TurretCam HL (8 Mp/2.8 mm)	90 m (295 ft)	36 m (118 ft)	18 m (59 ft)	9 m (29 ft)
TurretCam HL (8 Mp/4 mm)	117.5 m (385 ft)	47 m (154 ft)	23.5 m (77 ft)	11.6 m (38 ft)

Compliance with standards CE RoHS NDAA	Video and optics Resolution 5 MP version: up to 2880 × 1620 px @ 25 fps (3K UHD) 8 MP version: up to 3840 × 2160 px @ 20 fps (4K UHD) Lens 2.8 mm: 100°–110° viewing angle 4 mm: 75°–85° viewing angle Image processing True WDR hardware and software Video compression H.265, H.264 Bitrate 100 Mbps full-duplex Simultaneous live view Up to 5 channels Backlight IR illumination White light illumination Video stream RTSP Conformant with ONVIF® Profile G and S The device implements ONVIF® H.265 (HEVC) encoding, transmission of motion detection and AI recognition events, control over Wide Dynamic Range (WDR), and other image settings – not ONVIF® profile or add-on conformant. Storage Ajax NVR microSD card Up to 256 GB	Power supply Power supply unit 8–14 V== Ethernet 10/100 Mbps (RJ-45) Ethernet port PoE standard 802.3at/af Power consumption up to 8.5 W
Key features JetSparrow Proprietary Ajax protocol for fast and secure video transmission Motion detection Built-in software to detect motion in the frame Object recognition with built-in AI People Pets Vehicles Visual verification of Ajax system alarms Built-in digital microphone Activate sirens upon detection feature Automation scenarios Alarm verification Motion detection AI-powered recognition Detector alarm Automation scenarios		Enclosure Dimensions 103 × 98 × 98 mm 4.06" × 3.86" × 3.86" Weight 475 g 16.8 oz Colors black, white Protection class IP66 IK08
Installation Operating temperature range from –30 °C to +60 °C from –22 °F to +140 °F Operating humidity up to 90%		Complete set TurretCam HL Installation template Installation kit Quick start guide



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/turretcam-hl/

-  support@ajax.systems
-  @AjaxSystemsSupport_Bot
-  ajax.systems