MODEL #
CVT37IP5MP

COVERT ***NETWORK CAMERA***



5MP
RESOLUTION

5MP
2592(H)×1944(V)

3.7 mm

IR Up to 20M

Covert Camera

The 5MP covert security camera combines high-definition imaging with discreet design, making it the perfect solution for professional surveillance in sensitive environments. Equipped with a 3.7mm lens, it delivers clear and detailed visuals, ensuring nothing goes unnoticed. Its built-in Power over Ethernet (PoE) support allows for simple installation with just a single cable for power and data, reducing clutter and setup time. With infrared night vision reaching up to 20 meters, this camera guarantees reliable performance day and night, capturing clear footage even in total darkness. Ideal for offices, retail spaces, or any location where discreet yet powerful monitoring is required, this covert camera offers security without compromise.

2025 Global Surveillance Distribution, G.S.D Group, and G.S.D are registered trade names of Global Surveillance Distribution Group, Inc., a corporation under the laws of Canada and other jurisdictions. We reserve the right to change product designs, specifications, and features without notice or liability. Information is subject to change and is not guaranteed for accuracy or completeness.

COVERT NETWORK CAMERA

MODEL #
CVT37IP5MP

CAMERA

Effective Pixels	5MP 2592(H)×1944(V)
Resolution	**Main Stream @30fps** 5MP (2592*1944) **Sub Stream @30fps** 704*576
Frames Rates	NTSC :30fps(2560*1440)
Sensor	1/2.8" Sony 335 CMOS Sensor
Chipset	Dual core 32-bit DSP
Min Illumination	Color 0.001Lux@F1.2, B/W 0.0001 Lux@F1.2
Image Settings	WDR,BLC,DNR,AE,AGC,D&N,Mirror,Flip,etc.

VIDEO

Compression	H.265+/H.265/H.264
Streaming Capability	Supports dual stream, AVI format
Bitrate Range	0.1 – 4 Mbps
Frame Rate	Support 1~30fps adjust
Audio Codecs	G.711, AAC
Events	Motion Detection, Video Blind, Video Loss, Masking

NETWORK

Web Viewer	IE, Chrome, Firefox, Safari
Mobile App	N/A
Client Software	N/A
Ethernet	1× RJ45 (10/100BASE-T)
ONVIF Profile	YES
PoE	Yes

GENERAL

OSD Languages	English
IR Cut Filter	Dual-switch IR-cut filter
Lens	3.7 mm
IR Led Count	48
IR Range	20 m
Network Ports	1*DC Connector ,1* RJ45(10/100Mpps T)
Input Voltage	DC12V/PoE(802.3af/820.3at)
Power Consumption	IR On: 600mA max., IR Off: Less than 200mA
Operating Temp / Humidity	-10°C to +60°C / ≤ 90% RH
Dimensions	Ø120×70×46 mm
Weight	290 g

2025 Global Surveillance Distribution, G.S.D Group, and G.S.D are registered trade names of Global Surveillance Distribution Group, Inc., a corporation under the laws of Canada and other jurisdictions. We reserve the right to change product designs, specifications, and features without notice or liability. Information is subject to change and is not guaranteed for accuracy or completeness.

SECURITY. INNOVATION. RELIABILITY.

POWERED BY G.S.D GROUP INC.

At G.S.D Group, we design and deliver innovative, reliable, and high-performance security solutions that protect people, businesses, and critical infrastructure. From intelligent surveillance and access control to enterprise software and AI-powered technologies, we provide complete security ecosystems built for today's challenges and tomorrow's opportunities.

STAY CONNECTED

CONTACT US | YOUTUBE | LINKEDIN | NEWSLETTER

COMPLIANCE

CE MARKING | FCC CERTIFICATE | RoHS COMPLIANT | NDAA COMPLIANT

CONNECTION & INTERFACES

8525.89.40.00 — HS CODE

628308724376 — UPC CODE

ONVIF COMPLIANT

DOWNLOAD OUR APP: OV CONNECT

GET IT ON Google Play | Available on the App Store

WWW.GSDGROUPINC.COM **A CANADIAN ENTERPRISE**

2025 Global Surveillance Distribution, G.S.D Group, and G.S.D are registered trade names of Global Surveillance Distribution Group, Inc., a corporation under the laws of Canada and other jurisdictions. We reserve the right to change product designs, specifications, and features without notice or liability. Information is subject to change and is not guaranteed for accuracy or completeness.