MODEL #

IOBOX-08

NETWORK I/O CONTROLLER ***RELAY BOARD***



MULTI-CHANNEL RELAY OUTPUT

Provides multiple independently controllable relay outputs (8 or 16 channels) for triggering doors, alarms, lights, sirens, or other external devices.

FLEXIBLE POWER INPUT

Supports 12 VDC / 24 VDC or 12 VAC / 24 VAC power, allowing easy integration into existing low-voltage security and access control systems.

NORMALLY OPEN / NORMALLY CLOSED CONTACTS

Each relay supports NO and NC contact configurations for compatibility with a wide range of controlled equipment.

API-BASED REMOTE RELAY CONTROL

Enables relay activation via network commands or control logic initiated by NVR events, alarms, or system rules.

STANDARD NETWORK PROTOCOL SUPPORT

Supports TCP/IP, UDP, HTTP/CGI, and Modbus (RTU/ASCII/TCP/UDP) for seamless communication with NVRs, servers, and centralized platforms.

MULTIPLE COMMUNICATION INTERFACES

Equipped with Ethernet (RJ45), Wi-Fi, RS-485, and CAN Bus interfaces (Wiegand supported on the 16-channel model) for flexible system connectivity.

ADVANCED RELAY CONTROL FUNCTIONS

Supports delay timing, pulse/jog mode, interlock (mutual exclusion), linkage actions, and watchdog functions for reliable event handling.

DIGITAL INPUT AND OUTPUT EXPANSION

Includes digital input/output channels for connecting sensors, push buttons, alarms, or external triggers (expanded I/O on 16-channel model).

INDUSTRIAL-GRADE OPERATING DESIGN

Built for continuous operation in demanding environments with a wide operating temperature range (-10 °C to +85 °C).

COMPACT DIN-RAIL / PANEL-MOUNT FORM FACTOR

Designed for clean installation inside control panels, cabinets, or equipment racks commonly used in security deployments.

2025 Global Surveillance Distribution, G.S.D Group, and G.S.D are registered trade names of Global Surveillance Distribution Group, Inc., a corporation under the laws of Canada and other jurisdictions. We reserve the right to change product designs, specifications, and features without notice or liability. Information is subject to change and is not guaranteed for accuracy or completeness.

SPECIFICATIONS

Parameter	Voltage: 12VDC/24VDC/12VAC/24VAC Current: 1.5A@12VDC Power: 5W Switch Type: NO/NC Input/Output: Digital Input (DI) Digital Output (DO) Working Temperature: -10°C~85°C
Communication Interface	RJ45/WIFI/RS485/CAN BUS
Protocol	TCP server/client | UDP | HTTP GET CGI | Modbus-RTU/ASCII/TCP/UDP | Modbus-RTU Over TCP/UDP | Modbus-ASCII Over TCP/UDP | MQTT | CoAP | WIFI | CAN
Home Automation System	Automation System | Domoticz | Home assistant | OpenHAB | Red-Node
Functions	IP Watchdog (monitor other network device,it will reboot once the device offline) Transparent transmission: RS485/CANBUS transparent transmission to Ethernet/WiFi Jogging: control the relay board, it will recover the status within 1s Delay: control the relay board, it will recover the status during 1s or more Timing: set as month/week/day/hour/minute/second as a circle Switch Mutually Exclusive (Relay A and B is mutually exclusive, A is ON then B will be OFF automatically to protect the Motor) Mutually Control (Input 1 of device A control output 1 of device B) Linkage (any inputs can link any relays to active)
SDK	Program Manual | User Manual | C#/VC.net demo code | IP Finder | CGI test tool Ethernet test sample | RS485 test sample

2025 Global Surveillance Distribution, G.S.D Group, and G.S.D are registered trade names of Global Surveillance Distribution Group, Inc., a corporation under the laws of Canada and other jurisdictions. We reserve the right to change product designs, specifications, and features without notice or liability. Information is subject to change and is not guaranteed for accuracy or completeness.

SECURITY. INNOVATION. RELIABILITY.

POWERED BY G.S.D GROUP INC.

At G.S.D Group, we design and deliver innovative, reliable, and high-performance security solutions that protect people, businesses, and critical infrastructure. From intelligent surveillance and access control to enterprise software and AI-powered technologies, we provide complete security ecosystems built for today's challenges and tomorrow's opportunities.

STAY CONNECTED

CONTACT US | YOUTUBE | LINKEDIN | NEWSLETTER

CONNECTION & INTERFACES

8504.40.90.00

HS CODE

6 28308 72457 4

UPC CODE

DOWNLOAD OUR APP: OV CONNECT

GET IT ON Google Play

Available on the App Store

2025 Global Surveillance Distribution, G.S.D Group, and G.S.D are registered trade names of Global Surveillance Distribution Group, Inc., a corporation under the laws of Canada and other jurisdictions. We reserve the right to change product designs, specifications, and features without notice or liability. Information is subject to change and is not guaranteed for accuracy or completeness.