Specifications



Eaton SUPER725B

Protect It! 7-Outlet Surge Protector, 25 ft. Cord, 2160 Joules, Black Housing

General specifications	
PRODUCT NAME	Eaton Tripp Lite series Protect It surge protector
CATALOG NUMBER	SUPER725B
UPC	037332189844
PRODUCT LENGTH/DEPTH	10.3 in
PRODUCT HEIGHT	1.54 in
PRODUCT WIDTH	2.72 in
PRODUCT WEIGHT	2.89 lb
WARRANTY	Limited lifetime
COMPLIANCES	RoHS
CERTIFICATIONS	UL Listed UL 1449 NOM CSA Std. C22.2 cUL Listed CSA C22.2.
GLOBAL CATALOG	SUPER725B
PRODUCT TYPE	Surge protector

Product specifications

STORAGE HUMIDITY RANGE	5% to 95% RH
SURGE STYLE	ST - STRIP
SWITCHES	Two position on/off power switch
VOLTAGE COMPATIBILITY (VAC)	120
CIRCUIT BREAKER	15
FREQUENCY RATING	50/60 Hz
DIAGNOSTIC LED DETAILS	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
EMI / RFI FILTERING	Up to 20 dB
INPUT PLUG FEATURES	Right Angle (36D)
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
PROTECTION MODES	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
RECEPTACLE COLOR	BLACK
RECOMMENDED ELECTRICAL SERVICE	120V (110-125V)
SLOT OR HOLE MOUNT MEASUREMENT (CENTER TO CENTER)	Distance between slots = 70 mm; Distance between slot height = 24 mm
STORAGE TEMPERATURE RANGE	14° to 122°F (-10° to 50°C)
TRANSFORMER ACCOMMODATION	Transformer Accommodation
UL1449 LET THROUGH RATING	330 L-G, 400 L-N, 400 N-G
INPUT CORD DETAILS	SJT
INPUT CORD GAUGE (AWG)	14
CORD LENGTH	25 Foot
POWER CORD COLOR	Black
HOUSING COLOR	Black
OUTLET ORIENTATION	Single row of 5, plus 2 side mounted outlets
OUTLET SPACING	Between Standard Outlets = 29mm; Between Transformer Outlets = 48mm
OUTLETS MEASUREMENT (CENTER TO CENTER)	Between Standard Outlets = 29mm; Between Transformer Outlets = 48mm
MATERIAL	Plastic
INPUT PLUG TYPE	NEMA 5-15P
OUTPUT RECEPTACLES	5-15R
PACKAGE CONTENTS	SUPER725B Protect It! 7-Outlet Surge Protector, 25-ft. (7.62 m) Cord, Black Housing Owner's manual
INPUT NOMINAL	120 VAC

Resources

BROCHURES	Surge Protector and Power Strip Specification Brochure (English) Surge Protectors and Power Strips Brochure
DRAWINGS	Submittal Drawing for SUPER725B
MANUALS AND USER GUIDES	Owner's Manual for Protect It! Surge (Multi-language) Owner's Manual for Protect It! ® Surge Protectors (English)

VOLTAGE	120V AC
PRODUCT FEATURES	Diagnostic LED(s) Right-Angle Plug UL Certified Automatic Shut-Off Mounting Holes or Slots
PRODUCT HIGHLIGHTS	15A resettable circuit breaker prevents dangerous overloads 7 NEMA 5-15R outlets, including 3 for bulky transformers Filters out threatening EMI/RFI line noise $75,000 Ultimate Lifetime Insurance (U.S., Canada and Puerto Rico only) 25 ft. AC power cord with right-angle NEMA 5-15P plug Lifetime limited warranty (Worldwide) Surge suppression rating of 2160 joules
PLUG COLOR	White
AC SUPPRESSION JOULE RATING	2160
AC SUPPRESSION RESPONSE TIME	< 1 ns
CORD COLOR	Black
CORD GAUGE TYPE	• 14 gauge • SJT
MAXIMUM SURGE AMPS	144000
OPERATING HUMIDITY RANGE	10% to 90% RH
TOTAL OUTLETS	7

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.