



THE ALARM COMMUNICATION EXPERTS

TG-4

5G LTE-M RESIDENTIAL AND SMALL BUSINESS CELLULAR ALARM COMMUNICATOR



RESIDENTIAL BURGLARY & FIRE **COMMERCIAL BURGLARY**

Updated with a more modern 5G LTE-M cellular radio, more efficient use of power, and more options, the TG-4 is part of the full line of Telguard universal alarm communicators. The TG-4 can replace legacy Telco lines with reliable cellular signal reporting.

PRODUCT FEATURES

- Powered from either the included AC adapter or from the alarm panel's DC auxiliary power connection.
- Operates on LTE-M networks, for 5G longevity, lower power consumption, and better in-building penetration.
- Uses 256-bit encryption for robust security and widest compliance.
- Interfaces with alarm panels over the Telco DACT connection for universal compatibility (often called dial capture).
- Works with Telguard Virtual Modem for panel uploads and downloads (based on the capabilities of your panel).
- Add remote arming/disarming and more with the HomeControl Flex app.
- Easy-to-see LEDs for status, signal strength, and troubleshooting.
- American made and backed by award-winning, US-based tech support.
- TG-4B model is also available and includes an internal 12V battery.

You're in control when setting up and installing the TG-4. The communicator can be configured when you're in the office or on the road using the Telguard Tools app or the Telguard online dealer portal. Override the panel and send signals to your central station of choice — even when the installer code is unavailable.

UL Listings (AT&T & Verizon)

- 1023 Household Burglary
- 985 Household Fire
- 2610 Commercial Burglary

ULC Listings (AT&T Only)

- C1023 Household Burglary
- S545 Residential Fire
- S304 Commercial Burglary

Models by Carrier

- TG-4-A/TG-4B-A: AT&T (US & Canada)
- TG-4-V/TG-4B-V: Verizon (US Only)

Configurable Options

- Customer notification of alarm/trouble signals via app, text, or email
- Daily, weekly, or monthly self-test frequency
- One trip input and two output supervisory trip (STC) relays



HOMECONTROL FLEX

Compatible with
HomeControl Flex
interactive services.

Power Consumption

- Standby: 40mA @ 12VDC
- Transmit: 200mA @ 12VDC

Compatible Formats

CID, SIA, Radionics (11e/3a²,4), DMP, Pulse (4x2, 3x1), and more

Size (without antenna)

9.5 H x 4.5 W x 1.75 D in
(24.13 x 11.43 x 4.45 cm)



For the most current product specifications and UL/ULC certifications, visit telguard.com/tg-4. In Canada, cellular data may be carried by Rogers, Bell, Telus, or SaskTel.

800.229.2326 | 3225 Cumberland Blvd SE • Suite 300 • Atlanta, GA 30339 • USA | telguard.com

Protected by U.S. Patent Nos. 8,854,187 and 11,240,276. Additional patents pending.

©2025 Telguard | Telguard and the Telguard Logo are registered trademarks of Telular Corporation. | Telular is a business of AMETEK, Inc. All Rights Reserved.