

# INDOOR PIR DETECTORS

800.966.7839 / [www.optexamerica.com](http://www.optexamerica.com)

FLIPX SERIES: RESIDENTIAL / COMMERCIAL	<p><b>High Grade PIR for Residential &amp; Commercial Use</b></p> <p><b>FlipX Standard/Professional Series</b></p> <p>With unique 180° rotatable lens for customized wide or narrow detection</p> <p>Detection pattern can be customized from 85° wide for covering large open spaces, to 5° for covering long narrow passages or windows.</p> <p><b>Standard Models</b></p> <p>Residential &amp; light commercial</p> <p><b>FLX-S-ST 40ft, 85° wide, or 60ft narrow</b> Hardwired PIR Replaces OPTEX RX-40PI &amp; EX-35T</p> <p><b>FLX-S-DT 40ft, 85° wide, or 60ft narrow</b> Hardwired Dual-Tech</p> <p><b>Professional Models</b></p> <p>Commercial</p> <p><b>FLX-P-ST 50ft, 85° wide, or 80ft narrow</b> Hardwired PIR</p> <p><b>FLX-P-DT 50ft, 85° wide, or 80ft narrow</b> Hardwired Dual-Tech</p>	FLIPX SERIES: ADVANCED	<p><b>High Grade PIR for High-End Commercial Use</b></p> <p><b>FlipX Advanced Series</b></p> <p>With unique 180° rotatable lens &amp; anti-masking function</p> <p>Detection pattern can be customized from 85° wide to 5° narrow</p> <p><b>Advanced Models</b></p> <p>High-end / high-risk commercial</p> <p><b>FLX-A-AM 50ft, 85° wide, or 80ft narrow</b> Hardwired PIR, anti-masking Replaces OPTEX CDX-AM &amp; CDX-NAM</p> <p><b>FLX-A-DAM 50ft, 85° wide, or 80ft narrow</b> Hardwired Dual-Tech, anti-masking Replaces OPTEX CDX-DAM</p>	360° CEILING MOUNT	<p><b>360° Coverage for Residential or Commercial Applications</b></p> <p><b>Recessed Mount PIR</b></p> <p>Discreet PIR spot detection</p> <p><b>AP-360B(C) 20ft x 360°</b> Hardwired PIR 8'2" - 14'9" mounting height Light control option</p> <p><b>AP-360BR(C) 20ft x 360°</b> Battery-operated PIR 8'2" - 14'9" mounting height Battery saving timer</p> <p><b>SX Ceiling PIR</b></p> <p>Unique zoom function with twistable domed lens for easy adjustment</p> <p><b>SX-360Z 60ft x 360°</b> 8-16ft mounting height Triple-element detection 5 year limited warranty</p> <p><b>FX Ceiling PIR</b></p> <p>Specialized hard spherical lens for durability and precision detection</p> <p><b>FX-360 25-40ft, 360°</b> RFI immunity 20 V/m Patented multi-focus lens Selectable pulse count 2 or 4 Wireless options available</p>	HARSH ENVIRONMENT	<p><b>Heavy Duty PIR for Harsh Commercial Environments &amp; Industrial Applications</b></p> <p><b>CX-702 Series</b></p> <p>Sealed optics Multi-focus technology Maintained sensitivity Extreme false alarm resistance -4°F to +122°F</p> <p><b>CX-702</b> 70 x 70, 150 x 8ft Commercial with dual lens</p> <p><b>CX-702RS</b> 70 x 70, 150 x 8ft Commercial wireless-ready with dual lens</p> <p><b>CX-702Ri</b> 70 x 70, 150 x 8ft Wireless with transmitter &amp; battery</p>
	<p><b>Residential or Light Commercial</b></p> <p><b>AP-20NB(C) 20ft Range</b> Hardwired PIR Recessed wall/ceiling mount</p> <p><b>AP-20NBR(C) 20ft Range</b> Battery-operated PIR Recessed wall/ceiling mount</p> <p><b>AP2-20N 20ft Range</b> 8-12ft mounting height Wall/ceiling mount</p>		<p><b>CURTAIN PIR</b></p>				

# OUTDOOR PIR DETECTORS



SHIELD SERIES	<p><b>Flexible Performance &amp; Modern Design</b></p> <p><b>BX Shield Boundary Detector</b></p> <p>4 PIR technology, 2 on each side Independent detection settings per side</p> <p><b>BXS-ST 80ft, 40ft per side</b> Hardwired standard</p> <p><b>BXS-AM 80ft, 40ft per side</b> Hardwired with anti-masking</p> <p><b>BXS-R 80ft, 40ft per side</b> Wireless standard</p> <p><b>BXS-RAM 80ft, 40ft per side</b> Wireless with anti-masking</p>	SHIELD SERIES	<p><b>180° High &amp; Low Mount Detection</b></p> <p><b>WX Shield Panoramic Detector</b></p> <p>Up to 80ft total detection, 40ft on each side Independent detection settings per side Triple-layer detection with anti-masking</p> <p><b>WXS-AM 8 to 40ft, 180° range</b> Hardwired PIR, anti-masking</p> <p><b>WXS-DAM 8 to 40ft, 180° range</b> Hardwired Dual-Tech, anti-masking</p> <p><b>WXS-RAM 8 to 40ft, 180° range</b> Wireless PIR, anti-masking</p> <p><b>WXS-RDAM 8 to 40ft, 180° range</b> Wireless Dual-Tech, anti-masking</p>	SPOT / CURTAIN PROTECTION	<p><b>Dual PIR Sensors For Short &amp; Mid-Range Detection</b></p> <p><b>HX High Mount Series</b></p> <p><b>HX-40 40ft x 50ft</b> Standard high mount</p> <p><b>HX-40AM 40ft x 50ft</b> With anti-masking</p> <p><b>HX-40DAM 40ft x 50ft</b> Dual tech with anti-masking</p> <p><b>HX-40RAM 40ft x 50ft</b> Wireless ready</p> <p><b>HX-80N 80ft x 6ft</b> Long range standard</p> <p><b>HX-80NRAM 80ft x 6ft</b> Long range wireless ready</p>	FIT SERIES DUAL PIR	<p><b>Dual PIR Technology Sleek and Compact Design Intelligent Size Judging Function</b></p> <p><b>FIT Compact Series</b></p> <p>Weatherproof Animal tolerant Quick &amp; easy installation Affordable detection Built-in bracket with 190° rotation</p> <p><b>Wired Models</b></p> <p><b>FTN-ST 16.4 x 3.3ft / 6.6 x 1.6ft</b> Standard wired</p> <p><b>FTN-AM 16.4 x 3.3ft / 6.6 x 1.6ft</b> With anti-masking</p>
	<p><b>VX Shield Wide Angle Detector</b></p> <p>Intelligent PIR or Dual Tech Animal tolerant Active infrared anti-masking</p> <p><b>VXS-AM 40ft, 90° range</b> Hardwired PIR, anti-masking</p> <p><b>VXS-RAM 40ft, 90° range</b> Wireless PIR, anti-masking</p> <p><b>VXS-DAM 40ft, 90° range</b> Hardwired dual tech, anti-masking</p> <p><b>VXS-RDAM 40ft, 90° range</b> Wireless dual tech, anti-masking</p>		<p><b>Outdoor PIR For Lights &amp; Cameras</b></p> <p><b>LX Weatherproof Series</b></p> <p><b>LX-402 40ft x 50ft</b> With double conductive shield</p> <p><b>LX-802N 80ft x 6ft</b> Narrow long range</p>		<p><b>QXI High/Low Mount Series</b></p> <p><b>QXI-ST 40ft, 120° range</b> Hardwired PIR</p> <p><b>QXI-DT 40ft, 120° range</b> Hardwired Dual-Tech with anti-masking</p> <p><b>QXI-R 40ft, 120° range</b> Wireless PIR</p> <p><b>QXI-RDT 40ft, 120° range</b> Wireless Dual-Tech</p>		<p><b>Wireless Ready Models</b></p> <p><b>FTN-R 16.4 x 3.3ft / 6.6 x 1.6ft</b> Wireless ready</p> <p><b>FTN-RAM 16.4 x 3.3ft / 6.6 x 1.6ft</b> Wireless ready, with anti-masking</p> <p><b>FTN-R-PT 16.4 x 3.3ft / 6.6 x 1.6ft</b> Universal wireless transmitter compatible</p>

# WIRELESS ISERIES

With Inovonics EN1941 transmitter(s) & batteries pre-installed, installation time & cost are dramatically reduced. **Suggested Inovonics Receivers:** EN4232MR, EN4216R, EN4204R



BUILT-IN TRANSMITTERS & BATTERIES	<p><b>FTN-RAMi</b> Selectable 16.4ft x 3.3ft or 6.6ft x 1.6ft detection coverage Dual PIR technology with anti-masking</p>	<p><b>BX-80NRi</b> 80ft x 3ft total detection coverage, dual PIR technology 40ft x 3ft detection range per side</p>	<p><b>QXI-RDTi</b> 40ft by 120° detection range, high or low mount. With dual tech PIR &amp; microwave technology and anti-masking</p>
	<p><b>VXS-RAMi</b> 40ft by 90° detection range, PIR technology with anti-masking</p>	<p><b>BXS-RAMi</b> 80ft total detection coverage, Quad PIR technology, 40ft detection range per side with anti-masking. Dual-sided independent or simultaneous monitoring</p>	<p><b>WXS-RAMi</b> 8-40ft range, 180° panoramic coverage, high/low mount PIR with anti-masking. Dual-sided independent or simultaneous monitoring</p>
	<p><b>VXS-RDAMi</b> 40ft by 90° detection range, dual tech PIR &amp; microwave technology with anti-masking</p>	<p><b>HX-80NRAMi</b> 80ft x 6ft detection coverage High mount dual PIR technology, long &amp; narrow detection range</p>	<p><b>WXS-RDAMi</b> 8-40ft range, 180° panoramic coverage, high/low mount dual tech PIR &amp; microwave with anti-masking. Dual-sided independent or simultaneous monitoring</p>
	<p><b>HX-40RAMi</b> 40ft x 50ft detection coverage High mount dual PIR technology with anti-masking</p>	<p><b>SL-100TNRi</b> 100ft outdoor range, 5 year battery life</p>	<p><b>SL-350QFRI</b> 350ft outdoor range, 4 year battery life</p>
	<p><b>AX-100TFRI</b> 100ft outdoor or 200ft indoor range, 5 year battery life</p>	<p><b>SL-200TNRi</b> 200ft outdoor indoor range, 5 year battery life</p>	
<p><b>AX-200TFRI</b> 200ft outdoor or 400ft indoor range, 3 year battery life</p>			

# VISUAL SECURITY SYSTEM

## THE COMPREHENSIVE VISUAL ALARM MONITORING SOLUTION

INTELLIGENT VISUAL MONITORING

**Putting Eyes on Every Sensor – The Bridge Video Alarm Panel for Professionally Monitored Security Systems**

- Affordable, scalable, interior & exterior visual monitoring solution
- No central station hardware or setup fees, 5 second average delivery time to central station
- 30 minute install with CHeKT App, low cost of ownership
- Pre-alarm live view by zone
- ONVIF-S device compatible

**Kit contains:**  
(1) CKB-308  
(4) INS-CUBE

VISUAL VERIFICATION PIR CAMERA

**Easy integration with the Bridge ONVIF Conformant**

**InSight** Intelligent VCA with reliable outdoor PIR

**INS-QXI-ST**  
QXI-ST compatible  
40' detection  
120° wide angle

**INS-HX-80N**  
HX-80N compatible  
80'x6'7" detection  
43' default range\*

**Built-in PIR based camera 2-way audio talk down feature**

**INS-CUBE**  
Visual security indoor camera

\*The default detection distance on the HX-80N PIR is set to 43' (13m). If the device is set to detect at the maximum range of 80', additional illumination will be needed to cover the entire detection distance.

CHeKT AI IP CAMERAS	<p>DISTRIBUTED BY <b>OPTeX</b></p> <p><b>Deep-learning AI empowers cameras to learn, identify objects, and pinpoint human/vehicle types.</b></p>	<p>Central station integration with AI video alarm signal transmission when using the CHeKT Bridge.</p>	IP SPEAKERS
	<div style="display: flex; justify-content: space-around;"> <div> <p><b>CKIPAi5MP-D-MR</b> 5MP IR Dome AI IP Camera</p> </div> <div> <p><b>CKIPAi5MP-CB-FR</b> 5MP IR Compact Bullet AI IP Camera</p> </div> <div> <p><b>CKIPAi5MP-B-MR</b> 5MP IR Bullet AI IP Camera</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div> <p><b>CKIPAi5MP-T-MCA</b> 5MP Flashlight Full Color Turret AI IP Camera</p> </div> <div> <p><b>CKIPAi5MP-DL-TH-FR</b> Dual Thermal AI IP Camera</p> </div> <div> <p><b>CKIPC4MPT-12vDI</b> 4MP IP Turret Camera</p> </div> </div>	<p>DISTRIBUTED BY <b>OPTeX</b></p> <p><b>Combine video &amp; audio systems into a single proactive security solution Weatherproof IP67 design</b></p> <div style="display: flex; justify-content: space-around;"> <div> <p><b>CKIPS30W</b> CHeKT 30 Watt IP Horn Outdoor Speaker</p> </div> <div> <p><b>CKIPS15W</b> CHeKT 15 Watt IP Horn Outdoor Speaker</p> </div> </div>	

\*Please note: Camera series is only available to the North and South America market.

# ACTIVE INFRARED PHOTOELECTRIC DETECTORS & MOUNTING ENCLOSURES

<b>ENTRY</b>	<p><b>Dual (AX) &amp; Quad (SL) Single Frequency AIR PE beams for simple applications</b></p> <p><b>AX-70TN</b> 70ft outdoor/140ft indoor  <b>AX-130TN</b> 130ft outdoor/260ft indoor  <b>AX-200TN</b> 200ft outdoor/400ft indoor  <b>SL-200QN</b> 200ft outdoor/400ft indoor  <b>SL-350QN</b> 350ft outdoor/700ft indoor  <b>SL-650QN</b> 600ft outdoor/1300ft indoor</p>	<b>PROFESSIONAL</b>	<p><b>Quad Photoelectric detectors for perimeter &amp; point-to-point protection</b></p> <p><b>SL-200QDM</b> 200ft outdoor/400ft indoor  <b>SL-350QDM</b> 350ft outdoor/700ft indoor  <b>SL-650QDM</b> 650ft outdoor/1300ft indoor</p>	<b>MOUNTING ENCLOSURES</b>	<p><b>Customize Your Enclosures</b></p> <p>Create your own beam mounting enclosure from OPTEX. Start by picking your enclosure height, then choose mounting style, detector &amp; accessories.                  When a site plan is provided, OPTEX will build &amp; customize it to your specifications at no charge. We will even have it shipped directly to the job site for an easy &amp; time saving installation.</p> <p><b>6'6" Enclosures</b></p> <p><b>AX-TW200</b> Double sided free standing  <b>AX-TW200S</b> Single sided free standing  <b>AX-TW200M</b> Single sided wall mount</p> <p><b>3'3" Enclosures</b></p> <p><b>AX-TW100</b> Double sided free standing  <b>AX-TW100S</b> Single sided free standing  <b>AX-TW100M</b> Single sided wall mount</p> <p><b>AX-TWAA</b> Anti-climb top tamper for all AX-TW series enclosures  <b>AX-TWEB</b> Mounting bracket for poured concrete pad. Free standing enclosures only  <b>AX-TWEB-A</b> Mounting bracket for asphalt pad. Free standing enclosures only  <b>AX-TWH24V</b> 12 or 24 VDC enclosure heater  <b>AX-TWT</b> Enclosure thermostat  <b>AX-TWTH</b> 12 or 24VDC heater &amp; thermostat (kit)  <b>AX-TWLUXE</b> Light extension head for AX-TW series enclosures  <b>AX-TWCAM</b> CCTV extension head for AX-TX series enclosures</p>
	<p><b>Dual (AX) &amp; Quad (SL) 4 Channel Frequency AIR PE beams for perimeter &amp; point-to-point protection</b></p> <p><b>AX-100TF</b> 100ft outdoor/200ft indoor  <b>AX-200TF</b> 200ft outdoor/400ft indoor  <b>SL-200QDP</b> 200ft outdoor/400ft indoor  <b>SL-350QDP</b> 350ft outdoor/700ft indoor  <b>SL-650QDP</b> 650ft outdoor/1300ft indoor</p>		<p><b>Battery Powered, wireless quad beam photoelectric detectors for perimeter &amp; point-to-point protection</b></p> <p><b>SL-100TNR</b> Hybrid Powered 100ft outdoor/200ft indoor  <b>SL-200TNR</b> Hybrid Powered 200ft outdoor/400ft indoor.</p> <p><b>AX-100TFR</b> 100ft outdoor/200ft indoor  <b>AX-200TFR</b> 200ft outdoor/400ft indoor</p> <p><b>SL-350QFR</b> 350ft outdoor/700ft indoor.</p> <ul style="list-style-type: none"> <li>Lithium D cell batteries included</li> <li>Battery life 3-5 years, model based</li> <li>Works with most manufacturer transmitters</li> </ul>		<b>WIRELESS-READY</b>
<b>ADVANCED</b>	<p><b>AX-100TF</b> 100ft outdoor/200ft indoor  <b>AX-200TF</b> 200ft outdoor/400ft indoor  <b>SL-200QDP</b> 200ft outdoor/400ft indoor  <b>SL-350QDP</b> 350ft outdoor/700ft indoor  <b>SL-650QDP</b> 650ft outdoor/1300ft indoor</p>	<p><b>AX-100TFR</b> 100ft outdoor/200ft indoor  <b>AX-200TFR</b> 200ft outdoor/400ft indoor</p>			

## PowerG SERIES *Professional grade battery-powered, PowerG wireless detection solution by DSC*

PowerG

**BATTERY-POWERED PowerG RADIO**

**Battery-powered PowerG Beams by DSC streamline installations in remote locations, ensuring easy deployment without power constraints.**

**Available Models:**

**AX-200TFRPG**  
200ft photoelectric beam detector

**SL-350QFRPG**  
350ft photoelectric beam detector

- Reduced installation time with no wiring or trenching required.
- Easily integrates with existing security systems, even in remote locations.
- Utilizes DSC PowerG technology for long-range, secure wireless communication.
- Boasts two-way communication covering up to 1.24 miles in line-of-sight scenarios.
- Enhanced security with 128-bit AES encryption and extended battery life.
- Suitable for commercial applications requiring secure connectivity between devices and control panels.

## ACCESS CONTROL

<b>VEHICLE PRESENCE SENSOR</b>	<p><b>Virtual Loop Sensing Technology</b></p> <p>Reliably detect the presence of a stationary or moving vehicle while also having the ability to ignore most human traffic</p> <p><b>OVS-01GT 18ft range</b> Microwave &amp; ultrasonic vehicle presence sensor</p> <p><b>OVS-01CC 26ft range</b> Microwave vehicle presence sensor with car counting</p> <p><b>OVS-02GT 26ft range</b> Virtual Loop 2.0 Microwave &amp; ultrasonic vehicle presence sensor</p> <p><b>OVS-MPY</b> 28in mini post for road mounting — yellow</p> <p><b>OVS-MPB</b> 28in mini post for road mounting — black</p> <p><b>OVS-MPYcurb</b> 21in mini post for curb mounting — yellow</p> <p><b>OVS-MPBcurb</b> 21in mini post for curb mounting — black</p>	<b>REQUEST TO EXIT</b>	<p><b>Advanced Request to Exit &amp; Presence Detectors</b></p> <p><b>OP-08CBL &amp; OP-08CW</b> Black/white request to exist Flexible outdoor rated Fail safe or fail secure selectable 10 individual detection zones</p> <p><b>Reaction2</b> Microwave request to exit/activation sensor</p> <p><b>OA-72C</b> Architectural recess mount Presence detector/request to exit Presence timer can be adjusted Can mount up to 13ft high</p>	<b>SPECIAL APPLICATION</b>	<p><b>Special Application Automatic Door Sensors</b></p> <p><b>OA-FLEXT</b> Active Infrared Presence Sensor for Sliding/Swing Doors (Black)</p> <p><b>OS-12CT</b> Auto Setup Safety Mini AIR Beam (Control Only)</p> <p><b>SH-7MC</b> For the OS-12C: 1 Pair Sensor Heads &amp; 23' Cable</p> <p><b>SH-10MC</b> For the OS-12C: 1 Pair Sensor Heads &amp; 33' Cable</p>
	<p><b>Request to Exit &amp; Presence Detectors</b></p> <p><b>OP-08CBL &amp; OP-08CW</b> Black/white request to exist Flexible outdoor rated Fail safe or fail secure selectable 10 individual detection zones</p> <p><b>Reaction2</b> Microwave request to exit/activation sensor</p> <p><b>OA-72C</b> Architectural recess mount Presence detector/request to exit Presence timer can be adjusted Can mount up to 13ft high</p>		<p><b>Special Application Automatic Door Sensors</b></p> <p><b>OA-FLEXT</b> Active Infrared Presence Sensor for Sliding/Swing Doors (Black)</p> <p><b>OS-12CT</b> Auto Setup Safety Mini AIR Beam (Control Only)</p> <p><b>SH-7MC</b> For the OS-12C: 1 Pair Sensor Heads &amp; 23' Cable</p> <p><b>SH-10MC</b> For the OS-12C: 1 Pair Sensor Heads &amp; 33' Cable</p>		


REDSKAN detectors generate REDWALL event codes for Video Management Software (VMS) integration, and output standard analog alarm contact outputs simultaneously.

**Applications:** Power plants, substations, border protection, correction facilities, data centers, distribution centers, schools, airports, ports, water treatment plants, warehouses, museums & art galleries, financial institutions

## REDSKAN PRO SERIES


### Unique Features:

- Expanded detection coverage — RLS-50100V provides up to 530 ft vertical, 265 ft radius horizontal mount.
- Embedded video camera for visualizing your detection area.
- Built in analytics, including custom sensor settings per alarm zone & more.
- Event log function — Confirm events with event log & image.




### RLS-50100V

- 50 x 100 m (165 x 330 ft), 190° detection area
- High detection resolution: 0.125°
- Rectangular detection area
- Log function with camera
- Setting by Internet browser



### RLS-3060V

- 30 x 60 m (100 x 200 ft), 190° detection area
- Rectangular detection area
- Log function with camera
- Setting by Internet browser



SPECIALIZED DETECTORS FOR HIGH SECURITY APPLICATIONS

## REDSKAN mini-Pro SERIES

### Features

- Vertical & horizontal detection modes
- 65 x 65ft area with expandable 100ft, 95° detection coverage
- Precisely gauge object size, speed, & position within detection zone
- Independent detection zones and settings
- Configure settings via web browser
- Dynamic Event Filtering
- 0.125° high speed angular resolution
- Unaffected by light or temperature changes





### RLS-2020V

- With built-in FHD camera
- Camera view: H: 130°/V: 65°
- Indoor/outdoor use

### RLS-2020A

- Indoor/outdoor applications



## REDSKAN Mini SERIES

### Features

- Vertical & horizontal detection modes
- Multi-Angle Adjustment Shell Structure (M.A.S.S.)
- Unique detection algorithm
- Automatic area setting function
- Advanced area setting
- 4 adjustable detection areas on IP connection
- Total 3 outputs can be assigned for analog connection




### RLS-2020S

- 97.5ft (30m) radius arc detection, 95° angle
- Indoor/outdoor use
- Indoor high resolution
- Indoor throw-in mode

### RLS-2020i

- 65ft x 65ft, 95° detection area
- Indoor applications



SYNTHESIZED INTELLIGENT PIR



Rugged & durable long-range outdoor detector ideal for triggering remotely monitored, Event Driven CCTV systems




- SIP-3020, SIP-3020/5 100ft x 65ft with creep zone
- SIP-4010, SIP-4010/5 130ft x 33ft with creep zone
- SIP-404, SIP-404/5 130ft x 13ft with creep zone

**iSeries Battery-Powered Models Available**



Rugged & durable long range or wide angle outdoor detectors ideal for PTZ control & triggering remotely monitored, Event Driven CCTV Systems.



- SIP-5030 165ft x 100ft Built-in creep zone detector with ind. output
- SIP-100 330ft x 10ft Built-in creep zone detector with ind. output

RECOMMENDED ACCESSORIES



**AWT-3**  
Audible walk-tester for proper installation of SIP products



**AVF-1**  
Area view finder for visualization of detection of SIP products



**SIP-MINIHOOD**  
SIP-3020, 4010, 404  
**SIP-MIDIHOOD**  
SIP-5030, SIP-100  
Sun/snow shields



**SIP-HU**  
Heating unit for low temperature conditions (-40°F)