

5 MP HD IR Fixed Eyeball

Multi Format: CVI, TVI, AHD, CVBS



The R2-HD5MPEYE is a 5MP (2560 x 1920) eyeball camera constructed with a 2.8mm lens. This 5MP Camera is IP66 rated, provides HD Image quality and is ideal for a wide range of indoor/outdoor applications.

FEATURES

- 2.8MM LENS
- CVI, TVI, AHD, CVBS
- IR DISTANCE: 20M/66FT
- UTC & JOYSTICK CONTROLLABLE OSD
- IP66, 12VDC
- WARRANTY: 36 MONTHS
- PART #: R2-HD5MPEYE
- UPC: 840049305366
- DIMENSION: $\Phi 94 \times 84\text{MM}$ (3.7 $\times$ 3.3")
- WEIGHT: 0.79 LB



FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

Caméra Sphérique Fixe HD IR 5 Mpx

Multiformat: CVI, TVI, AHD, CVBS



Le modèle R2-HD5MPEYE est une caméra sphérique 5 Mpx (2560 x 1920) dotée d'un objectif 2,8 mm. Elle est homologuée IP66, offre une qualité d'image HD et convient à une vaste gamme d'applications intérieures ou extérieures.

FEATURES

- | | |
|---|---|
| <ul style="list-style-type: none">● OBJECTIF DE 2,8 MM● CVI, TVI, AHD, CVBS IR● DISTANCE (IR) : 20 M/66 PI● COMMANDE D’AFFICHAGE À L’ÉCRAN DE TYPE MANETTE ET UTC● IP66, 12VCC● GARANTIE : 36 MOIS | <ul style="list-style-type: none">● PART #: R2-HD5MPEYE● UPC: 840049305366● DIMENSION: $\Phi 94 \times 84\text{MM}$ (3.7 $\times$ 3.3")● WEIGHT: 0.79 LB |
|---|---|



CAMERA

IMAGE SENSOR	1/3" PROGRESSIVE SCAN CMOS
EFFECTIVE PIXELS	2560(H) x 1920(V)
SCANNING SYSTEM	PROGRESSIVE
ELECTRONIC SHUTTER	AUTO/MANUAL, PAL:1/25-1/10000S, NTSC:1/30-1/10000S
MIN. ILLUMINATION	COLOR:0.05LUX@(F1.2,AGC ON) ; B/W:0LUX@(IR LED ON)
S/N RATIO	MORE THAN 48DB
IR RANGE	UP TO 20M
IR ON/OFF CONTROL	AUTO/MANUAL
IR LEDS	18PCS
OSD JOYSTICK	SUPPORTED
UP THE COAX	SUPPORTED
PAN/TILT/ROTATION RANGE	PAN:0°-360°; TILT:0°-90°; ROTATION:0°-360°

LENS

LENS TYPE	FIXED
IRIS	FIXED IRIS
FOCAL LENGTH	2.8MM
F NUMBER	F2.0
ANGLE OF VIEW	H: 92.3°, V: 50.8°
FOCUS CONTROL	FIXED

VIDEO

RESOLUTION	5MP (2560×1920)
FRAME RATE	PAL:20FPS ,NTSC:20FPS
DAY/NIGHT	EXT /AUTO /COLOR/MONO
OSD MENU	SUPPORTED
WIDE DYNAMIC RANGE	DWDR, OFF/ON
NOISE REDUCTION	2D DNR(MANUAL): 1-16
White Balance	Auto
BLC	SUPPORTED
MIRROR	SUPPORTED

GENERAL

POWER SUPPLY	DC12V±10%
POWER CONSUMPTION	MAX. 4W (12V DC, IR ON)
OPERATING TEMPERATURE	-10 °C ~ 55 °C (14°F ~ 131 °F)
OPERATING HUMIDITY	LESS THAN 85% RH
INGRESS PROTECTION	IP66
CERTIFICATIONS	CE/FCC
CASING	METAL
DIMENSIONS	Φ94×84MM (3.7×3.3")
NET WEIGHT	0.36KG (0.79LB)

**FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.**